

# AD Belt U7

## Overview

---

**Frequency Band**

UHF 860 - 960 MHz

---

**Chip**

NXP UCODE 7

---

**Antenna Dimensions**

70 x 10 mm / 2.76 x 0.39 in

---

**International Standard**

ISO 18000-6C, EPC Class 1 Gen 2

---

**Industry Segments**

Apparel  
Industrial Applications

---

**Applications**

Brand Protection  
Supply Chain Management  
Home Essentials

---


**RoHS**

EU Directive 2011/65/EC and  
Directive (EU) 2015/863

---

**REACH**

Regulation (EC) No 1907/2006



## Compact size and high performance in item-level tagging

Our AD Belt UCODE 7 inlays and tags are designed for global retail, industry and supply chain applications with excellent performance, including in close coupling environments.

AD Belt UCODE 7 inlays and tags have a compact 76 mm / 3 inch form factor, which can be easily converted into end-application usage, and are available in dry, wet and label / sticker delivery formats. They are available with the NXP UCODE 7 chip that offers a 96-bit Tag Identifier (TID) factory locked with a 48-bit unique serial number factory-encoded into TID.


AD Belt with the NXP UCODE 7 IC, used in retail applications, is included on the approved inlay list for boxed electronics by the RFID Research Center at the University of Auburn, and complies with categories A, B, D, F, G, K, I, M, N and Q. Furthermore, it meets GS1 Tagged-Item Performance Protocol (TI PP) Tagged-Item Gratings M10B S15B, M15B S15B and M20D S15D for the retail supply chain,retailers and suppliers.

Our inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment.


## Technical features

Chip	NXP UCODE 7
EPC and User Memory	128-bit and n/a
TID Memory	96-bit / 48-bit unique serial number
Product Code	3003011 / IL-602767
Delivery Format	Wet inlay
Die-Cut Dimension	73 x 13 mm 2.87 x 0.51 in
Inlay Substrate	PET
Face Sheet	-
Standard Pitch	20 mm / 0.787 in
Web Width	80 mm / 3 in
Core Size	76 mm / 3 in
Quantity / Reel	20,000 pcs/reel
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F

## Orientation sensitivity



## Read range



All graphs are indicative: performance in real life applications may vary.

### Contact information

[rfid.averydennison.com/contact](http://rfid.averydennison.com/contact)  
+1-678-617-2359

Connect with us on:



© 2022 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

**Warranty:** Please refer to Avery Dennison standard terms and conditions: [rfid.averydennison.com/termsandconditions](http://rfid.averydennison.com/termsandconditions)

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

