

AD Microblock ICODE SLIX

Overview

Frequency Band

HF 13.56 MHz

Chip

NXP ICODE SLIX

Antenna Dimensions

8 x 8 mm / 0.315 x 0.315 in

International Standard

ISO 15693

Industry Segments

Pharma and Healthcare

Applications

NFC
Product Authentication

RoHS

EU Directive 2011/65/EU and
2015/863 Compliant

REACH

Regulation (EC) No 1907/2006



Small, powerful square inlay for use where space is at a premium

AD Microblock ICODE SLIX is Avery Dennison's smallest square form factor inlay, offering excellent performance for healthcare applications, healthcare authentication and item-level tagging in situations where space for an inlay is limited. Conforming to NFC Type 5, which offers support for the ISO/IEC 15693 specification, the tag also offers the flexibility of NFC, which allows it to be read by any suitable modern smartphone. Microblock ICODE SLIX is significantly smaller in size than previously launched products, offering enhanced performance through its use of copper. It uses NXP's ICODE SLIX, which offers 896-bit of user memory.

The tag is currently available as a wet inlay, but can be offered in other delivery formats. Microblock ICODE SLIX is compliant with ISO 9001:2012 Quality Management and ISO 9001:2012 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs.

Technical features

Chip	NXP ICODE SLIX
User Memory	896-bit
Product Code	3007552
Delivery Format	Wet inlay
Die-Cut Dimension	10 x 10 mm / 0.394 x 0.394 in
Inlay Substrate	PET
Face Sheet	Clear PET
Inlay Liner Material	Siliconized paper
Standard Pitch	16 mm / 0.63 in
Web Width	20 mm / 0.787 in
Core Size	76 mm / 3 in
Quantity / Reel	5,000 pcs/reel
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F

Contact information

rfid.averydennison.com/contact

North America: +1-866-903-7343 (toll free US)

International: +1-678-617-2359

Connect with us on:



© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

