



BELT

Compact Size and High Performance in Item-level Tagging

SMARTRAC's BELT inlays and tags are designed for global retail, industry and supply chain applications with excellent performance, including in close coupling environments.

BELT inlays and tags have a compact 76mm / 3 inch form factor, which can be easily converted into end-application usage, and are available in dry, wet and paper tag delivery formats.

The BELT products are available with the Impinj Monza R6 and R6-P chips that come with an Autotune feature, which helps the BELT product to work at peak efficiency, even in rapidly changing environments. BELT with the Monza R6 chip offers unique TID and enables pre-serialized EPC. Inlays with Monza R6-P offer additional features such as add-on user memory and on-demand memory configuration as well as a kill function and easy access control to change tag information for store data, if required.

BELT with the Impinj Monza R6 and R6-P IC, used in retail applications, is included on the approved inlay list for boxed electronics by the ARC (Auburn Radio Compliance Center), and complies with categories A, B, C, D, K, I, M, N, Q. Furthermore, it meets GS1 Tagged-Item Performance Protocol (TIPP) Tagged-Item Gradings M10B S15B, M15B S15B and M20D S15D for the retail supply chain, retailers and suppliers, and is recommended by Impinj for the fixed-base xArray system.

SMARTRAC's inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment.

Overview

Operating Frequency

860 - 960 MHz

Integrated Circuit (IC)

Impinj Monza R6 & R6-P

Antenna Size

70 × 10 mm (2.7 × 0.4 in)

Die-cut Size

73 × 13 mm (2.9 × 0.5 in)

International Standards

- ▶ EPC Class 1 Gen 2
- ISO 18000-6C



Application Areas

- ▶ Brand Protection
- ▶ Industry
- ▶ Retail
- ▶ Supply Chain Management

BELT

Compact Size and High Performance in Item-level Tagging

Technical Features			
IC + Memory	Size	Format	Sales Code
Impinj Monza R6 96 bit	73 × 13 mm / 2.9 × 0.5 in	Wet	3005058
	70 × 10 mm / 2.8 × 0.4 in	Inlay	3004228
	73 × 13 mm / 2.9 × 0.5 in	Paper Tag	3004230
	73 × 17 mm / 2.9 × 0.7 in	Paper Tag	3004527
Impinj Monza R6-P 128 bit EPC + 32 bit user 96 bit EPC + 64 bit user	73 × 13 mm / 2.9 × 0.5 in	Wet	3005068
	70 × 10 mm / 2.8 × 0.4 in	Inlay	3005067
	73 × 13 mm / 2.9 × 0.5 in	Paper Tag	3005065
	73 × 17 mm / 2.9 × 0.7 in	Paper Tag	3005066
Web Width	80 mm / 3.15 in		
Operating Temperature	-40 °C to +85 °C / -40 °F to +185 °F		
Adhesive	Acrylic, water borne adhesive		
Qty/Reel	5,000 pcs / 15,000 pcs		
Core Size	76 mm / 3 in		
Shelf Life	+20 °C, 50 % RH / 68 °F, 50 % RH - minimum 2 years from the date of manufacturing		



All the graphs are indicative: performance in real life applications may vary. The data has been determined based on calculations for transmitters with a 2W ERP output power level.

SMARTRAC N.V. · Strawinskylaan 851 · 1077 XX Amsterdam · The Netherlands

Phone: +31 20 30 50 150 · Fax: +31 20 30 50 155

Contact: Sales & Customer Service

www.smartrac-group.com/contact



© 2018 SMARTRAC N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.

