



<b>Dimensions</b>	95 x 8.15 mm
<b>Operating Frequency</b>	Global (860 – 960 MHz)
<b>RF Protocol</b>	ISO-18000-6C, EPC Class 1, Gen 2
<b>Chip</b>	Impinj Monza R6
<b>EPC Memory</b>	96 bit
<b>TID Memory</b>	48-bit unique serialized TID Number

**Common Applications**

Supply Chain, Inventory and Logistics  
Apparel and other item-level retail  
Return Transport Units

**Toll free US 866-903- RFID (7343) / rfid.info@averydennison.com**  
**International +1-770-965-0807**

PART NUMBER	RF600591	RF600592	RF600593
Format	Dry Inlay – Wide Web	Dry Inlay	Wet Inlay
Antenna dimensions (CDxMD)	3.74 x 0.32 in (95 x 8.15 mm)	3.74 x 0.32 in (95 x 8.15 mm)	3.74 x 0.32 in (95 x 8.15 mm)
Die-cut dimensions	N/A	N/A	3.885 x 0.44 in (98.7 x 11.2 mm)
Inlay substrate material	White PET	White PET	White PET
Inlay-to-liner adhesive	N/A	N/A	S-490
Liner material	N/A	N/A	40# SCK
Face Sheet	N/A	N/A	N/A
Standard pitch	0.625 in (15.875 mm)	0.625 in (15.875 mm)	0.625 in (15.875 mm)
Standard web width	4.75 in (120.65 mm)	3.875 in (98.425 mm)	4.125 (104.77 mm)
Total thickness over chip	7-9 mils (178-229 microns)	7-9 mils (178-229 microns)	9 -11 mils (229-279 microns)
Operating temperature	-40 to 185F (-40 to 85C)	-40 to 185F (-40 to 85C)	-40 to 185F (-40 to 85C)
RoHS	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant
Quality assurance	100% read tested with-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked
Un-wind direction	Inlay-side Out	Inlay-side Out	PS Inlay-side Out
Core size with adaptor insert	6 in (152.4 mm)	6 in (152.4 mm)	3 in (76.2mm)
Maximum roll outer diameter (not to exceed)	13 in (330.2 mm)	13 in (330.2 mm)	13 in (330.2mm)
Average # of units per roll	20,000 good +/- 10%	20,000 good +/- 10%	20,000 good +/- 10%
Rev	01	01	01

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

**Warranty:** Please refer to Avery Dennison RFID standard terms and conditions.

**Product Information:** Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

**Trademark statement:** Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit [www.rfid.averydennison.com](http://www.rfid.averydennison.com).



<b>Dimensions</b>	95 x 8.15 mm
<b>Operating Frequency</b>	Global (860 – 960 MHz)
<b>RF Protocol</b>	ISO-18000-6C, EPC Class 1, Gen 2
<b>Chip</b>	Impinj Monza r6-P
<b>EPC Memory</b>	128/96 bits
<b>USER Memory</b>	32/64 bits
<b>TID Memory</b>	48-bit unique serialized TID Number

**Common Applications**

Supply Chain, Inventory and Logistics  
Apparel and other item-level retail  
Return Transport Units

Toll free US 866-903- RFID (7343) / [rfid.info@averydennison.com](mailto:rfid.info@averydennison.com)  
International +1-770-965-0807

PART NUMBER	RF600772	RF600776	RF600773
Format	Dry Inlay – Wide Web	Dry Inlay	Wet Inlay
Antenna dimensions (CDxMD)	3.74 x 0.32 in (95 x 8.15 mm)	3.74 x 0.32 in (95 x 8.15 mm)	3.74 x 0.32 in (95 x 8.15 mm)
Die-cut dimensions	N/A	N/A	3.885 x 0.4 in (98.7 x 11.2 mm)
Inlay substrate material	White PET	White PET	White PET
Inlay-to-liner adhesive	N/A	N/A	S-490
Liner material	N/A	N/A	40# SCK
Face Sheet	N/A	N/A	N/A
Standard pitch	0.625 in (15.875 mm)	0.625 in (15.875 mm)	0.625 in (15.875 mm)
Standard web width	4.75 in (120.65 mm)	3.875 in (98.425 mm)	4.125 (104.77 mm)
Total thickness over chip	7-9 mils (178-229 microns)	7-9 mils (178-229 microns)	9 -11 mils (229-279 microns)
Operating temperature	-40 to 185F (-40 to 85C)	-40 to 185F (-40 to 85C)	-40 to 185F (-40 to 85C)
RoHS	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant
Quality assurance	100% read tested with-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked
Un-wind direction	Inlay-side Out	Inlay-side Out	PS Inlay-side Out
Core size with adaptor insert	6 in (152.4 mm)	6 in (152.4 mm)	3 in (76.2mm)
Maximum roll outer diameter (not to exceed)	13 in (330.2 mm)	13 in (330.2 mm)	13 in (330.2mm)
Average # of units per roll	20,000 good +/- 10%	20,000 good +/- 10%	20,000 good +/- 10%
Rev	01	01	01

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

**Warranty:** Please refer to Avery Dennison RFID standard terms and conditions.

**Product Information:** Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

**Trademark statement:** Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit [www.rfid.averydennison.com](http://www.rfid.averydennison.com).